

# Lumenis Array™ LaserLink™

Pattern Scanning Laser Technology



Array™  
LaserLink™

# With Unique Heads Up Display the Physician does not Lose Sight of the Patient's Retina

## Heads Up Display

Heads up display shows changes of settings as text on the retina, seen through the oculars of the slit lamp.



## 3D Micromanipulator

The Array 3D Micromanipulator allows the adjustment of laser power, number of spots, titrate mode and micromanipulation of the laser beam - all in the palm of your hand.



## Intuitive Touch Screen

Intuitive touch screen duplicates the functions of the laser's remote control. The fully adjustable monitor can be set on either side of the slit lamp. It is easily reached and visualized for treatment set up and during the procedure.





# Array™ LaserLink™

## Pattern Scanning Laser Technology

Pattern Scanning Laser can reduce photocoagulation treatment time by as much as 60%\*

Pattern scanning laser provides enhanced uniformity of laser application, shorter treatment time, and less discomfort to the patient.

The Array™ LaserLink™ offers pattern scanning capabilities compatible with Lumenis laser systems and popular slit lamps, versatility of wavelengths, various adjustable patterns and a range of laser spot sizes.

### Compatibility

#### Links with Lumenis lasers:

- Vision One
- Novus Spectra

#### Attaches to most popular slit lamps:

- Lumenis 980
- Zeiss SL130
- Zeiss 30SL

### Versatility

#### With Lumenis multi-wavelength technology, Array™ delivers any of the following wavelengths:

- Green: 532 nm
- Yellow: 577 nm
- Red: 659 nm

#### Array treatment options:

- Single spot
- Pulse mode
- Various patterns

Array™ offers a range of laser spot sizes from 50 µm to 1000 µm in single spot mode, and 100 µm to 500 µm in pattern scanning mode.

### Sensibility

- **Intuitive touch screen**
- **Custom 3D micromanipulator**
- **Heads up display**, shows important parameter changes as text on the retina
- **Frame mode** displays a precise outline in the area the pattern will be administered
- **Titrate mode** is used to establish appropriate pattern laser parameters with a single spot
- **Contact lens menu** lists commonly used lenses for calculation of laser spot size on the retina
- **Spot size on retina** tells doctor actual parameter of treatment

**Risks and warnings:** Array is intended solely for use by trained physicians. It is contraindicated for eyes with severe media opacities. Risks include increased macular edema and bleeding in areas of neovascularization. Refer to the operator manual for a complete list of intended use, contraindications and risks.

\* Retina. 2010 Mar;30(3):452-8. Comparison of laser photocoagulation for diabetic retinopathy using 532 - nm standard laser versus multispot pattern scan laser. Nagpal M, Marlecha S, Nagpal K.



# Array™ LaserLink™

## Keeps the Target in View

### Maintain Focus on the Patient



#### Eyes Forward Control

Control and verify treatment parameters without moving from the slit lamp oculars or losing sight of the target retina



#### Heads Up Display

- Confirms changes to treatment parameters
- Displays text on the retina
- Modified parameters are projected as text onto the retina



#### Unique Array 3D Micromanipulator

- Controls laser parameters and micromanipulation
- Adjustable for left or right hand use



#### Intuitive Touch Screen

- Fully adjustable monitor
- Is easily reached and visualized for treatment set up and procedure



## Customize Treatment to Meet the Patient and Physician Needs



### Continuous Variable Spot Size

- Single spot from 50  $\mu\text{m}$  to 1000  $\mu\text{m}$
- Pattern mode from 100  $\mu\text{m}$  to 500  $\mu\text{m}$
- Customized treatment for the particular disease state and tissue response



### Variety of Adjustable Patterns

Includes single spot and six types of patterns:

- Square: 2 to 5 spots per edge
- Line: 2 to 5 spots per line, up to 4 lines in shape
- Triangle: 3 or 5 spots per edge
- Circle: Single adjustable ring
- Quarter of a circle: 1 or 3 adjustable arcs
- Half of a circle: 1 or 3 adjustable arcs



### Up to 5 Preset Protocols

- Retains favorite settings in memory
- Includes settings such as fundus lens selection, laser power, spot size, spot spacing, number of spots and duration



### Selectable Spot Spacing

- For a circle, from 0-3 times the spot diameter
- For other patterns, from 0.25-3 times the spot diameter



### Next Generation ClearView™ Filters

- Utilizes photopic balanced coating to eliminate color distortion
- Optimizes white light transmission or “brightness” of the physician’s view



### Patented SureSpot™ Optics

- Ensures that the focal point of the laser beam is maintained on the retina
- Minimizes power density on the cornea and lens for increased safety

# Lumenis Array™ LaserLink™ Specifications

<b>Patterns</b>	Single spot, square, line, triangle, circle, quarter circle, half circle
<b>Spot Size</b>	Single spot: 50,100, 125, 150, 175, 200, 250, 300, 400, 500,1000 µm 3-ring quarter circle and 3-ring half circle: 100 µm and 200 µm Other Patterns: 100, 125, 150, 175, 200, 250, 300, 400, 500 µm
<b>Spot Spacing</b>	Single-ring circle: x 0.0, 0.25, 0.50, 0.75, 1.00, 1.50, 2.00, 2.50, 3.00 Other patterns: x 0.25, 0.50, 0.75, 1.00, 1.50, 2.00, 2.50, 3.00
<b>Spot Duration</b>	10, 20, 30, 40, 50 ms for pattern   10 - 3000 ms for single spot
<b>Power</b>	532 nm: 50 - 2000 mW   577 nm: 50 - 1500 mW   659 nm: 50 - 800 mW*

## Compatible lasers

<b>Vision One</b>	532 nm (green)   577 nm (yellow)   659 nm (red)*
<b>Novus Spectra / Spectra DP</b>	532 nm (green)

## Compatible slit lamps

<b>Off Axis Illumination Slit Lamps</b>	Lumenis 980   Zeiss 30SL   Zeiss SL130
<b>Electrical requirements</b>	100 - 240 VAC, 50/60 Hz, 150 W max

## General specifications

<b>Weight</b>	Console: 3.5 kg   Array LaserLink™ Module: 5 kg
<b>Equipment classification</b>	US Class II, EU Class I

\* Relevant only for single spot

Lumenis® Certified Service | USA Toll-free 1-877-LUMENIS (1-877-586-3647)

 Manufactured by Lumenis Inc.  
1870 South Milestone Drive  
Salt Lake City, UT 84104 USA  
Tel +801-656-2300  
Fax +801-656-2429

 Lumenis (Germany) GmbH  
Heinrich-Hertz-Str 3 D-63303  
Dreieich-Dreieichenhain  
GERMANY  
Tel +49 (0) 6103 8335 0

**AMERICAS**  
San Jose, CA, USA  
Tel +1 408 764 3000  
+1 877 586 3647  
Fax +1 408 764 3999

**EMEA**  
Dreieich Dreieichenhain,  
Germany  
Tel +49 6103 8335 0  
Fax +49 6103 8335 300  
Roma (RM), Italy  
Tel +39 06 90 75 230  
Fax +39 06 90 75 269  
Hertfordshire, UK  
Tel +44 20 8736 4110  
Fax +44 20 8736 4119

**JAPAN**  
Tokyo, Japan  
Tel +81 3 4431 8300  
Fax +81 3 4431 8301

**ASIA / PACIFIC**  
Beijing, China  
Tel +86 10 5737 6677  
Gurgaon, India  
Tel +91 124 422 07 95  
Kowloon, Hong Kong  
Tel +852 217 428 00  
Fax +852 272 251 51



ISO 13485 CERTIFIED

[www.lumenis.com/Ophthalmology](http://www.lumenis.com/Ophthalmology)

© 2017 All Rights Reserved. The Lumenis Group of Companies. PB-2005744 Rev B

 **Lumenis®**  
Energy to Eye Care